

Single Scissors

Our largest product group, single scissors, is available in a range of designs, all equally flexible, stable and ergonomically well thought-out. Lift tables are commonly used as a means for handling materials directly on the factory floor or as a lorry loaders outdoors at a loading dock.

- ▶ T-model lift tables are Swedish-made and of the highest quality. They can be customized based on your own needs
- ▶ C-models are our affordable options and come in standard design with a range of accessories
- ▶ Special dimensions and other customizations can be quoted on request
- ▶ See page 83-89 for stainless alternatives



TL 2000

C-model	Art. no.	Capacity kg	Lift stroke mm	Lowest height mm	Length mm	Width mm	Lift time sec	kW	Weight kg pack. incl.	Note
▶ CR 500	36473	500	600	160	900	600	12	0,37	100	
▶ CR 1000	515215	1000	600	160	900	700	23	0,37	130	
▶ CL 1001*	36045	1000	820	180	1200	800	15/26	0,75	180	
▶ CL 1500	524827	1500	820	200	1300	1200	17	1,5	300	
▶ CL 2000	36474	2000	820	200	1300	800	17	1,5	250	
▶ CL 2000B	613210	2000	820	200	1300	1000	17	1,5	264	
▶ CB 1200	524828	1200	1000	210	1500	1200	17	1,5	330	
▶ CB 1500	36475	1500	1000	210	1500	800	17	1,5	280	
▶ CB 1500B	36478	1500	1000	210	1500	1000	17	1,5	300	

*1-phase free of charge

T-model	Art. no.	Capacity kg	Lift stroke mm	Lowest height mm	Length mm	Width mm	Lift time sec	kW	Weight kg pack. incl.	Note
▶ TR 501	609945	500	600	160	900	700	12	0,37	140	
▶ TR 1002	608179	1000	600	160	900	700	22	0,37	150	
▶ TL 1000	34964	1000	820	180	1300	700	15	0,75	180	
▶ TL 1000H**	613230	1000	930	180	1350	800	15	0,75	214	
▶ TL 1000B	32920	1000	820	180	1300	800	15	0,75	190	
▶ TL 1000XB	32925	1000	820	180	1300	1000	15	0,75	200	
▶ TL 1001B	33024	1000	820	180	1200	800	15	0,75	190	
▶ TL 2000	22010	2000	820	200	1300	800	17	1,5	235	
▶ TL 2000B	22011	2000	820	200	1300	1000	17	1,5	250	
▶ TL 2000XB	512633	2000	820	200	1300	1200	17	1,5	285	
▶ TL 3000	33560	3000	820	250	1300	800	26	1,5	300	
▶ TB 2000	22253	2000	1000	220	1500	1000	26	1,5	305	
▶ TB 2000B	22254	2000	1000	220	1500	1200	26	1,5	325	
▶ TM 1000	32970	1000	1100	180	1700	700	27	0,75	225	
▶ TM 1500	22012	1500	1100	230	1700	1000	17	1,5	300	
▶ TM 1500B	33145	1500	1100	230	1700	1200	17	1,5	330	
▶ TM 3000	33180	3000	1100	250	1700	900	27	1,5	390	
▶ TM 6000*	33810	6000	1100	300	1700	900	32	3,0	530	
▶ TA 1000	33335	1000	1300	200	2000	800	16	1,5	315	
▶ TA 2000	34230	2000	1300	230	2000	900	30	1,5	385	
▶ TA 4000	33860	4000	1300	350	2000	1200	27	3,0	650	
▶ TS 2001	606524	2000	1500	250	2200	1200	27	1,5	550	
▶ TS 2001B	610969	2000	1500	250	2200	1500	27	1,5	590	
▶ TS 4000	33430	4000	1500	350	2200	1200	27	3,0	690	
▶ TS 4000B	33440	4000	1500	350	2200	1500	27	3,0	750	
▶ TT 3000	32662	3000	1700	300	2500	1300	27	3,0	700	
▶ TT 6000	614680	6000	1600	450	2500	1300	40	3,0	1100	
▶ TP 3000	514564	3000	2000	400	3000	1500	38	3,0	1200	
▶ TP 6000	614660	6000	2000	500	3000	1500	55	3,0	1450	
▶ TP 10000	615100	10000	1800	550	3000	1500	36	5,5	2030	
▶ TX 4000	615130	4000	2750	500	4000	1500	69	3	1930	

*External hydraulic power pack excluding cover **Flat steel plate scissor arms

▶ = normally kept-in-stock products for quick delivery

Heavy Duty lift tables

The HD-series lift tables meet the severe requirements of the toughest category of the lift table standard EN 1570-1, category 5. That means that the lift table needs to perform a minimum of 512,000 lift cycles while carrying the rated load. That is four and sixteen times as many lift cycles as conventional lift tables that are produced in category 1 and category 3 respectively.

The powerful lube for life bearings creates the conditions for uninterrupted maintenance-free operations. The exclusive design with the robust scissor provides extreme stability in all directions.

The lift table's modularized construction makes it easy to adjust its size for a bespoke, unique solution.

The HD-series is the solution that enables the highest productivity and accessibility without operational interruptions.

- ▶ Meets the requirements of the lift table standard EN 1570-1, category 5
- ▶ More than 512 000 lift cycles with rated load, durability tested in our own facilities
- ▶ Lube for life bearings
- ▶ Maintenance free, designed to run 24/7 – 365
- ▶ Extremely compact design
- ▶ Suitable for system integration
- ▶ Cost-effective option for larger platform
- ▶ Lifting capacity 2000 kg



EN 1570-1 CATEGORY 5
Highest durability rating available for lift tables

